



Since 2010

High Tech Service Srl

Via Case Nuove, 15 – 21018 Sesto Calende (VA)
Tel./Fax. 0331.024813 – 320.3346026
P.i. 03184040123
e.mail: info@hightechservicesrl.it
www.hightechservicesrl.it

COMBINED 5 OPERATIONS MOD. 300C

Type: Combined 5 operations
Brand: Sicar
Model: 300C



C300

Combinata 5 lavori

- Pialla a filo
- Pialla a spessore
- Cavatrice
- Toupie
- Sega circolare con inclinazione



C300

Combined 5 operations

- Surface planer
- Thicknesser
- Mortiser
- Spindle moulder
- Circular saw



C300 è l'anello di congiunzione tra la linea hobby e la gamma professionale. È stata pensata per l'artigiano che non vuole rinunciare alla SICUREZZA, PRECISIONE e AFFIDABILITÀ. C300 diventerà il mezzo attraverso il quale potrai dare forma alle tue creazioni in legno!

C300 is the connecting link between the hobby line and the professional line. It has been thought for the particularly demanding wood craftsman, who doesn't want to give up to safety, precision and reliability. It's the right means by which you can give shape to your wood creation!

• 2



Technical Data:

| | |
|---|----------------------------|
| Planer | |
| Working table | 300 x1500 mm |
| Cutter block diameter | 70 mm |
| Cutter block rotation speed | 5700 r.p.m. |
| Dimensions knives (3 knives) | 300 x 20 x 3(300x25x3) mm |
| Max table adjustment | 4 mm |
| Thicknesser | |
| Working table | 300 x 660 mm |
| Feed Speed | 7 m/1' |
| Working height | 4-220 mm |
| Mortiser | |
| Working table | 250 x 500 mm |
| Longitudinal/Trasversal/Vertical stroke | 205/95/90 mm |
| Churk | 0 – 16 mm |
| Circular saw | |
| Working tables | 220 x 1000 mm |
| Shaft rotation/Engraver speed | 4500/7000 r.p.m. |
| Blade diameter | 250 x 30 mm |
| Cutting height at 45°/90° | 50/80 mm |
| Cutting width parallel fence | 500 mm |
| Engraver blade diameter | 90 x 22 mm |
| Shaper | |
| Working tables | 220 x 1000 mm |
| Shaft rotation speeds | 2000/3100/4400/7000 r.p.m. |
| Standard shaft diameter | 30/35/50 mm |
| Shaft vertical stroke | 115 mm |
| Max tool diameter | 160 mm |
| Max tenoning depth | 55 mm |
| Standard accessories | |
| 3-phase motor power | 3,0 – 2,2 Hp – Kw |
| Carriage dimensions | 1250 x 315 mm |
| Optional accessories | |
| Single – phase motor | 3,0 – 2,2 Hp - Kw |
| Increased 3-phase motor | 4,0 – 3,0 Hp – Kw |
| Dimension carriage | 1600/1800/2000/2200 mm |
| Main package | 2200 x 1590 x 875 mm |
| Net weight | 560 Kg |